

# WVI40141-DL-A

## 4MP Dual Light HDCVI Fixed-focal Bullet Camera



- 1/2.9" 5MP progressive scan CMOS
- 4 MP 2560H\*1440V@25fps Resolution.
- Switchable CVI / TVI / AHD / CVBS
- Auto electronic shutter, auto exposure and auto white balance
- Comply with the seismic structure design of CCTV,IP66
- Internal audio pick-up with the maximum audio collection range of 5 meters (with audio)

| Specification          |  |
|------------------------|--|
| Signal support         | CVI output as default<br>Switchable CVI / TVI / AHD / CVBS |
| sensor                 | 1/2.9" 4M pixel CMOS                                       |
| Out put Resolution     | 2560H*1440V (4MP)  |
| Shutter                | Auto/ 1/25~1/25000   |
| Lens                   | 4.0 mm F1.6  |
| Synchronization system | Internal synchronization                                   |
| Scanning system        | Progressive scan   |
| S/N                    | ≥ 50dB   |
| Day/night              | Day&Night mode ICR IR filter                               |
| White balance          | Auto tracking of white balance                             |
| Auto gain              | Supported  |
| 3D noise reduction     | Supported  |
| Backlight compensation | Supported  |
| \                      | Digital WDR  |
| IR range               | 15-20m   |
| Video output           | 1.0Vp-p Composite video output, 75Ω                        |



# WVI40141-DL-A

4MP Dual Light HDCVI Fixed-focal Bullet Camera

| Specification         |   |
|-----------------------|---|
| Power supply          | DC12V ±20%                                |
| IR LED details        | 3pcs white/IR led(twin-core light inside) |
| Audio                 | YES(Coaxial audio)                        |
| Operation Temperature | -30°C-- +70°C                             |
| Operation Humidity    | 0% - 90%                                  |
| Waterproof Class      | IP66                                      |

## Dimensions

