

Bullet Network Camera




MODEL : WIP-B041P-LED

Specifications



Feature

- 4MP High Performance CMOS
- 2560*1440 Resolution
- 4 mm Lens
- 8PCS Warm LED
- Full color night vision
- Metal Housing IP66 Water proof
- Build-in Mic
- ONVIF 2.4
- Supports 3D DNR/AWB/Exposure
- Support humanoid and vehicle detection
- Support PoE



Main Parameters

Image Sensor	4.0 MP CMOS GC4653
Signal System	PAL/NTSC
Effective Resolution	2560H*1440V
Minimum Illumination	0.1lux, 0 lux with IR
Shutter Speed	AUTO/ 1/25-1/10000sec
Lens	4 mm (2.8/6 mm optional)
Horizontal Field of View	82.6° (3.6 mm), 54.4° (6 mm)
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 90°, Rotate: 0° to 360°
WDR	D-WDR
White balance	Support auto white balance
Image Enhancement	3N-DNR/D-WDR/BLC/HLC
General Function	Mirror, Privacy shelter, Human Detection, Voice recording, Restart
OSD	Support OSD setting, drag the position freely

Intelligent function

Electronic fence	Support humanoid and vehicle detection, When enter into warning area, camera
Cross-border detection	Support humanoid and vehicle detection, Support A→B, B→A, A↔B direction
Departure detection	Set the detection area, the device will alarm after the personnel leave for a certain period of time, and the alarm will stop after returning
Passenger flow statistics	Supports the detection of the number of people entering and leaving
Voice broadcast	Support linkage voice broadcast, voice content can be customized recording
Light alarm	Support linkage equipment lighting alarm function
NVR linkage	Support large-screen linkage video recorder, local voice, AI recording, push and

Hardware

Compression	H.264, H.265
Main stream	4MP(2560*1440)/
Sub-stream	1: 488P(800*488), 2: D1(704*576), 3: 360P(640*360), 4: CIF(352*288)
Frame rate	4MP 25fps
Video Adjustment	Brightness, saturation, chroma, contrast and sharpness adjustment

General

Ethernet	RJ-45 10M/100M self-adaption
Protocol	ONVIF, P2P, CGI, HTTP, TCP/IP, IPv4, RTSP, UDP, NTP, DHCP, DNS, IP
Access protocol	Support ONVIF/private protocol/CGI
User/Host	Up to 4 users
Client	IOS, Android, Windows

Communication Interface	1-port RJ45 10M/100M self-adaptive Ethernet port
On-Board Storage	N/A
Reset Button	N/A
Operating Conditions	-4° F to 140° F (-20° C to 60° C), humidity: 90% or less (non-condensation)
Power Supply	12V DC / 48V DC PoE
Power Consumption	Maximum: 6 W
IR Range	Up to 65 ft (20 m)
Protection Level	IP66
Dimensions	233 mm x 76 mm x 68mm
Weight	Approximately 0.6 kg

