

Bullet Network Camera

MODEL : WIP50313



Feature

5 MP Bullet Camera Dual light Night vision

- Light indicator for network status (This feature is limited to non-PoE models)
- Spotlight on motion detection
- Full-Color with Dual Smart Illumination
- Support Humanoid Detection
- Built-in Mic and Speaker
- With built-in PoE
- Equipped With unique VQC (Video Quality Catalyst) Technology
- Support Micro SD Card (512 GB)

Specifications

| Video | |
|----------------------------|--|
| Imaging devices | 1/3" CMOS Sensor |
| Max Resolution | 2560x1792 |
| Effective Pixels | 5.0MP |
| Compression Standard | H.264/H.265 |
| Framerate | 25fps |
| Bitrate | Main Stream: 317Kbps ~ 8Mbps Sub Stream: 68Kbps~272Kbps |
| SNR (dB) | 52dB |
| Min. Illumination | 0Lux (light ON) |
| Lens | |
| Interface Type | M12 |
| Lens | 3.6mm |
| FOV | H 80°, V 41.1°, D 94.6° |
| Function | |
| Audio Codec | G.711U/G.711A (default) |
| Exposure Control | Auto |
| White Balance | Auto |
| Gain Control | Auto |
| Digital 3D Noise Reduction | Support |
| OSD Information Setting | Large font OSD, OSD flashing on alarm, OSD position settings |
| SNTP | Support |
| Schedule Reboot | Support |
| Smart Defog | Support |
| Motion Detection | Support Humanoid Detection |
| Image Setting | Support Saturation, Brightness, Contrast, Sharpness adjustment |
| Image Style | Standard, Soft, Transparent |
| Day and Night Function | Auto, Always Black & White, Always Color, Scheduled Color |
| Privacy Mask | Support up 8 areas |



Bullet Network Camera

MODEL : WIP50313

Specifications

| | |
|---------------------------|--|
| Night Vision Optimization | Support |
| DWDR | Support |
| Screen Settings | Screen mirroring, Screen flipping |
| IP Adaptation | Support automatic adaptation of IP address (Optional) |
| Intelligent Analysis | Support Region Intrusion Detection, Line Crossing Detection, Video Blocking Detection, People Counting |
| Alarm Method | Email Alarm, Client Alarm |
| Remote Operation | System, Audio and Video, Image, Alarm, Network management, Storage management, Intelligent Analysis |
| Audio Function | Built-in Mic and Speaker |
| SD Card | Support (512G) |
| VQC Technology | Support |
| Network | |
| Ethernet | 10/100Mbps Ethernet |
| Stream | 2x Streams |
| Network Protocols | HTTP, TCP/IP, UDP, ICMP, RTSP, RTP, RTCP, SMTP, DHCP, DNS |
| ONVIF | Standard ONVIF |
| Network Transmission | CloudSEE 2.0 |
| Browser | IE8+, Chrome18+, Firefox5.0+, Safari5.02+ |
| User | Up to 13 Users |
| App | Support iOS/Android |
| General | |
| Lights | 4 White LEDs + 4 IR LEDs |
| IR Distance | Up to 50 Meters |
| Waterproof Level | IP67 |
| Power Supply | DC12V or PoE (IEEE802.3af) |
| Power Consumption | <3W (During Day); <6W (At Night) |
| Working Temperature | -20°C ~ 60°C |
| Working Humidity | 10% ~ 90% Rh |
| Color/Material | Black and White/Plastic |
| Dimensions (WxHxD) | 95x95x175mm |
| Weight | 290g |
| Installation Method | Wall or ceiling mount (Bracket Optional) |

