

Digital Video Recorder

MODEL : WVR071

Feature

XVR 4CH 5M-N 5-in-1

- TVI / AHD / CVBS / CVI / IP 5-in-1 Function, Multi-mode Input, Support HD Analog Video Encoding, Support HD Analog + HD Network Video Input, Support Pure HD Network Video Input.
- Support Various Mobile Phone Monitoring (iPhone/Android)
- Support Multiple Web Browsers (IE/Chrome/Firefox/Safari)
- Support VGA,HDMI Output At The Same Time
- Support Coaxial Audio



Specifications

| | |
|---------------------|---|
| System | |
| Compression | H.265 |
| O/S | Embedded Linux O/S |
| Video and Audio | |
| Video Input | 4CH BNC + 6CH IPC |
| Preview Ability | 4*5MN@20fps (4 in 1) *HDTVI 4*4MN@20fps (4 in 1) *HDTVI ,HDCVI, AHD; 4*1080N@25fps (4 in 1) *HDTVI ,HDCVI, AHD; |
| Coding Ability | 4*5MN@12fps (4 in 1) 4*4MN@12fps (4 in 1) 4*1080N@15fps (4 in 1) |
| Decoding Ability | 4*5MN@12fps (4 in 1) 4*4MN@12fps (4 in 1) 4*1080N@15fps (4 in 1) |
| Video Output | 1CH VGA;1CH HDMI |
| Channel Mode | Support any channel mode combination (5MN analog + 5M digital) |
| Audio In & Out | 1/1, RCA 4CH coaxial audio input + 6 channels network audio |
| Video Standard | PAL/NTSC |
| Storage | |
| SATA | 1x SATA Interface |
| Capacity | Up to 8TB Max. |
| Backup Mode | USB |
| Playback and Backup | |
| Video Playback | Auto/Timing/ Motion detection |
| Sync Playback | 4CH |
| Search Mode | Point-in-time search, calendar search, event search, channel search |
| Network | |
| Ethernet | 10 / 100 Mbps,1 RJ45 |
| Network Function | TCP/IP, DHCP, DDNS, NTP, SMTP |
| Interoperability | ONVIF Standard |
| Smart Phone | iPhone, Android |



Digital Video Recorder

MODEL : WVR071

Specifications

| Hardware | | |
|----------------------|--|---|
| Network Interface | | 1x RJ45 |
| USB Interface | | 2x USB2.0 |
| PTZ Interface | | Not Support |
| Controlling Device | | Mouse |
| Alarm Input | | Not Support |
| Alarm Output | | Not Support |
| Special | | |
| Multi-Screen Display | | 1, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16 |
| Alarm Method | | Email Alarm |
| Digital Zoom | | Support |
| Two-Way Talk | | Not Support |
| Alarm Snapshot | | Support |
| Intelligent Analysis | | Support Motion Detection |
| General | | |
| Power Supply | | DC12V /2A |
| Consumption | | ≤ 15 W |
| Working Temperature | | -10°C ~55°C |
| Working Humidity | | 10% ~ 90% Humidity |
| Dimensions | | 250x223x42mm |
| Weight | | 800g |



| Index | Description | Index | Description |
|-------|-------------|-------|-------------|
| 1 | Video In | 6 | RJ45 |
| 2 | Video Out | 7 | USB |
| 3 | HDMI | 8 | Power |
| 4 | Audio In | 9 | VGA |
| 5 | Audio Out | | |

