

# Smart Wi-Fi camera

MODEL : WIOT1018G-3MP



## Feature

- 3MP 1/3" CMOS
- Easy to pair: Scan QR code or via AP mode to pair
- Pan/Tilt
- Motion tracking
- Motion detection to reduce false alarm, adjustable sensitivity level
- Two way audio, echo cancellation
- 3DNR,DWDR
- 850nm infrared LED, effective distance of 8 meters
- Real-time monitoring
- Cloud storage supported

## Specifications

| Video&Audio           |                                    |
|-----------------------|------------------------------------|
| Resolution            | 3MP 2304*1296                      |
| Chipset               | T31                                |
| Lens                  | Focal length: 4.0mm                |
| FOV                   | 94.6°                              |
| Encoding              | H.264                              |
| Two way audio         | Two way audio, echo cancellation   |
| Audio input           | Mic                                |
| Audio output          | Speaker                            |
| Night vision          | IR-CUT auto switch                 |
| Night vision distance | 8-10m                              |
| Wireless connection   | 2.4 GHz Wi-Fi IEEE 802.11 b/g/n;   |
| Motion detection      | Support                            |
| Microphone            |                                    |
| Signal to noise ratio | ≥58dB                              |
| Sensitivity           | -36dB± 2dB                         |
| Speaker function      |                                    |
| Speaker function      | Support                            |
| Local Storage         |                                    |
| TF card               | Max to 128GB(TF card not included) |
| Value added service   |                                    |
| Cloud storage         | Optional                           |
| Amazon Alexa          | Optional                           |
| Google assistant      | Optional                           |
| Power                 |                                    |
| Power port            | TYPE-C                             |
| Power                 | DC 5V1A                            |
| Certificate           |                                    |
| Certificate           | CE/FCC compliant                   |
| Operating environment |                                    |
| Working temperature   | -10°C ~ 50°                        |
| Working humidity      | 10~95% non-condensing              |

