

Smart Wi-Fi camera

MODEL : WIOT1035



Feature

- Dual-band connection
- Display on both mobile and monitor screen
- Monitor screen of low-power consumption, support dual-screen viewing
- Transmission distance up to 200m
- One-button call, two-way audio
- Motion/noise/crying detection
- Danger zone selection
- Feeder reminder
- Temperature & humidity detection
- Lighting comfort, lullaby play

Specifications

Camera	
Image Sensor	1/2.8" 3Megapixel CMOS
Effective Pixels	2304(H) x 1296(V)
Shutter	1/20~1/10,000s
Min. Illumination	Color 0.1Lux@F2.0, Black/White 0.01Lux@F2.0
IR Distance	Night visibility up to 10m
Day/Night	Auto(ICR)/Color/B&W
WDR	DWDR
Lens&FOV(H/V/D)	3.6mm@F2.0, 91°/50°/110°
Video&Audio	
Compression	H.264
Bit Rate	32Kbps~2Mbps
Frame Rate	1~25fps
Dual Stream	Yes
Audio Input/Output	Built-in mic/speaker
Network	
Alarm Trigger	Intelligent human/noise/crying detection
Wireless Security	64/128-bit WPA/WPA2, WPA-PSK/WPA2-PSK, WPS
Communication Protocol	HTTP, DHCP, DNS, TCP/IP, RTSP
Interface Protocol	Private
Wireless	2.4G WIFI (IEEE802.11b/g/n)
Mobile Phone OS	iOS 9 or later, Android 5 or later
Security	AES128
Max. User Access	6
General	
Pan/Tilt	Pan: 0°~345°, tilt: -8°~52°
Lighting Comfort	Continuous/running/breathing light, full-color setting
Operating Temperature	-20 °C to 50 °C
Power Supply	DC 5V/1A
Power Consumption	Max. 4.5W
Storage	SD card(Max.128GB), Cloud storage, NVR
Dimensions	φ80 x 153mm
Net Weight	282g



Smart Wi-Fi camera

MODEL : WIOT1035 (Monitor)



Specifications

Image	
Image Resolution	720P (1280 x 720)
Screen Size	5" LCD
Wireless	IEEE802.11ah
Transmission Distance	Up to 200m
Audio	
Way to Intercom	Two way audio
Power	
Battery Capacity	3000mAh rechargeable
Working Current	460mA
Stand-by Current	12mA
Value added service	
Operating Temperature/Humidity	-20~50°C / < 90% without condensation
Storage	SD card (Max. 128GB)
Dimensions	157 x 45 x 81mm
Net Weight	180g

